



SPECIFICATION:
CONTACT RATING: 6A 250VAC, 10A 125VAC
INSULATION RESISTANCE: 500V d.c. for 1 min.
ELECTRIC STRENGTH: 2000V a.c. for 1 min.

NO	DESCRIPTION	MATERIAL	QTY
1	PIN	BRONZE, NICKEL	2
2	COVER	ABS 777B	1
3	GROUND COVER	ABS 777B	1
4	CONTACT	BRONZE, NICKEL	2

核准日期 Date

設計 Designed By

比例尺 Scale

26 JUN 2003

C.J HUANG

1:1

核准 Approved By

繪圖 Drew By

單位 UNIT

J.F. WANG

C.T WANG

m/m

核准日期 Date

設計 Designed By

比例尺 Scale

26 JUN 2003

C.J HUANG

1:1

核准 Approved By

繪圖 Drew By

單位 UNIT

J.F. WANG

C.T WANG

m/m

TOLERANCES

- 0.5MM-5MM=±0.2MM
- 5MM-30MM=±0.4MM
- 30MM-120MM=±0.6MM
- 120MM-315MM=±1.0MM
- 315MM-1000MM=±1.6MM
- 1000MM-2000MM=±2.4MM

REF. NO.

11330A

EUROPEAN TRAVEL

ADAPTOR PLUG

大 廣 有 限 公 司

DA KOANG CO., LTD.

修正日期

增加規格說明

修正說明

J.F. WANG

C.T WANG

m/m

DA KOANG CO., LTD.

EUROPEAN TRAVEL
ADAPTOR PLUG

REF. NO.