



3	SHELL	RUBBER	TOLERANCE		SIGNATURES		DATE	大廣有限公司 DA KOANG CO., LTD.	
2	SCREW	F8	1 - H 2 - H 3 - H 4 - H 5 - H 6 - H 7 - H 8 - H 9 - H 10 - H 11 - H 12 - H 13 - H 14 - H 15 - H 16 - H 17 - H 18 - H 19 - H 20 - H 21 - H 22 - H 23 - H 24 - H 25 - H 26 - H 27 - H 28 - H 29 - H 30 - H 31 - H 32 - H 33 - H 34 - H 35 - H 36 - H 37 - H 38 - H 39 - H 40 - H 41 - H 42 - H 43 - H 44 - H 45 - H 46 - H 47 - H 48 - H 49 - H 50 - H 51 - H 52 - H 53 - H 54 - H 55 - H 56 - H 57 - H 58 - H 59 - H 60 - H 61 - H 62 - H 63 - H 64 - H 65 - H 66 - H 67 - H 68 - H 69 - H 70 - H 71 - H 72 - H 73 - H 74 - H 75 - H 76 - H 77 - H 78 - H 79 - H 80 - H 81 - H 82 - H 83 - H 84 - H 85 - H 86 - H 87 - H 88 - H 89 - H 90 - H 91 - H 92 - H 93 - H 94 - H 95 - H 96 - H 97 - H 98 - H 99 - H 100 - H		DRAFT: YangYangRui CHECKED: HuSongXue		05.11.08		
1	BODY	Cu	1 - H 2 - H 3 - H 4 - H 5 - H 6 - H 7 - H 8 - H 9 - H 10 - H 11 - H 12 - H 13 - H 14 - H 15 - H 16 - H 17 - H 18 - H 19 - H 20 - H 21 - H 22 - H 23 - H 24 - H 25 - H 26 - H 27 - H 28 - H 29 - H 30 - H 31 - H 32 - H 33 - H 34 - H 35 - H 36 - H 37 - H 38 - H 39 - H 40 - H 41 - H 42 - H 43 - H 44 - H 45 - H 46 - H 47 - H 48 - H 49 - H 50 - H 51 - H 52 - H 53 - H 54 - H 55 - H 56 - H 57 - H 58 - H 59 - H 60 - H 61 - H 62 - H 63 - H 64 - H 65 - H 66 - H 67 - H 68 - H 69 - H 70 - H 71 - H 72 - H 73 - H 74 - H 75 - H 76 - H 77 - H 78 - H 79 - H 80 - H 81 - H 82 - H 83 - H 84 - H 85 - H 86 - H 87 - H 88 - H 89 - H 90 - H 91 - H 92 - H 93 - H 94 - H 95 - H 96 - H 97 - H 98 - H 99 - H 100 - H		APPROVAL:			大廣有限公司 DA KOANG CO., LTD.	
ITEM	DESIGNATION	MATERIAL	1 - H 2 - H 3 - H 4 - H 5 - H 6 - H 7 - H 8 - H 9 - H 10 - H 11 - H 12 - H 13 - H 14 - H 15 - H 16 - H 17 - H 18 - H 19 - H 20 - H 21 - H 22 - H 23 - H 24 - H 25 - H 26 - H 27 - H 28 - H 29 - H 30 - H 31 - H 32 - H 33 - H 34 - H 35 - H 36 - H 37 - H 38 - H 39 - H 40 - H 41 - H 42 - H 43 - H 44 - H 45 - H 46 - H 47 - H 48 - H 49 - H 50 - H 51 - H 52 - H 53 - H 54 - H 55 - H 56 - H 57 - H 58 - H 59 - H 60 - H 61 - H 62 - H 63 - H 64 - H 65 - H 66 - H 67 - H 68 - H 69 - H 70 - H 71 - H 72 - H 73 - H 74 - H 75 - H 76 - H 77 - H 78 - H 79 - H 80 - H 81 - H 82 - H 83 - H 84 - H 85 - H 86 - H 87 - H 88 - H 89 - H 90 - H 91 - H 92 - H 93 - H 94 - H 95 - H 96 - H 97 - H 98 - H 99 - H 100 - H		1 - H 2 - H 3 - H 4 - H 5 - H 6 - H 7 - H 8 - H 9 - H 10 - H 11 - H 12 - H 13 - H 14 - H 15 - H 16 - H 17 - H 18 - H 19 - H 20 - H 21 - H 22 - H 23 - H 24 - H 25 - H 26 - H 27 - H 28 - H 29 - H 30 - H 31 - H 32 - H 33 - H 34 - H 35 - H 36 - H 37 - H 38 - H 39 - H 40 - H 41 - H 42 - H 43 - H 44 - H 45 - H 46 - H 47 - H 48 - H 49 - H 50 - H 51 - H 52 - H 53 - H 54 - H 55 - H 56 - H 57 - H 58 - H 59 - H 60 - H 61 - H 62 - H 63 - H 64 - H 65 - H 66 - H 67 - H 68 - H 69 - H 70 - H 71 - H 72 - H 73 - H 74 - H 75 - H 76 - H 77 - H 78 - H 79 - H 80 - H 81 - H 82 - H 83 - H 84 - H 85 - H 86 - H 87 - H 88 - H 89 - H 90 - H 91 - H 92 - H 93 - H 94 - H 95 - H 96 - H 97 - H 98 - H 99 - H 100 - H		DRAFT: YangYangRui CHECKED: HuSongXue		
REV	PART NO. & SAMPLE NO.	DATE	BY	APPROVAL:			TITLE		Tip Plug(Screw Type) Color:Red,Black
A	1045			SHEET		1:1	MM	REV	
B				OF		1:1	MM	REV	CUSTOMER