



ELECTRICAL CHARACTERISTIC

①	CONTACT RESISTANCE: $\leq 10m\Omega$
②	INSULATION RESISTANCE: $\geq 20M\Omega$
③	WITHSTAND VOLTAGE: DC500V
④	CURRENT RATING: 0.5A/DC300V
⑤	OPERATING TEMPERATURE: $-250^{\circ}C \sim 80^{\circ}C$

4	NUT	Fe
3	WASHER	Fe

2	PLASTIC HANDLE	ABS
1	PIN	BRASS
ITEM	DESIGNATION	MATERIAL

REV	PART NO. & SAMPLE NO.	DATE	BY	TOLERANCE	SIGNATURES	DATE
A	3038			0 - 10 ±0.05 10 - 99 ±0.5 100 - 999 ±1.0 1000 - 9999 ±100.00 10000 - 99999 ±1000.00	DRAFT: YangYongRui CHECKED: HuGongXue	13-05-2013

大廣有限公司
DA KOANG CO., LTD.

REV	PART NO. & SAMPLE NO.	DATE	BY	APPROVAL:	SCALE	UNIT	REV	TITLE	CUSTOMER
A	3038				1:1	mm	∅	Banana Jack 125V. 3A,4mm Use. (Red,Black,Yellow,Purple)	
B				SHEET	OF				