



ELECTRICAL CHARACTERISTIC

(1)	CONTACT RESISTANCE: ≤20mΩ
(2)	INSULATION RESISTANCE: ≥10MΩ
(3)	WITHSTAND VOLTAGE:DC300V
(4)	CURRENT RATING:5A/DC150V
(5)	OPERATING TEMPERATURE: -30℃~60℃

7	BODY	Cu	
6	NUT	Zn	
5	EARTHING PATCH	Fe	
4	WASHER	Fe	
3	PLASTIC HANDLE	ABS	
2	WASHER	Cu	
1	SHELL	ABS	
ITEM	DESIGNATION	MATERIAL	
REV	PART NO.& SAMPLE NO.	DATE	BY
A	3110		
B			

TOLERANCE	0 - 10 10 - 99 100 - 999 1000 - 9999 10000 - 99999	±0.05 ±0.5 ±10.0 ±100.00 ±1000.00
-----------	--	---

SIGNATURES	DATE
DRAFT: cheng huan	10.01.15
CHECKED:	

大廣有限公司
DA KOANG CO., LTD.

SHEET	SCALE	UNIT	REV
OF	1:1	mm	Ø

APPROVAL:	TITLE
	Binding Post-Small Size (Red/Black)

CUSTOMER