



**MATERIALS:**

- A. BOOT: PE + 2L
- B. MIDDLE HOOD: HIPS (PH-88)
- C. METAL SHELL:
- COPPER NICKEL PLATED
- D. INSULATOR: NYLON 6 + G.F.
- E. PIN CONTACT:
- BRASS SILVER PLATED

	7.0ø	BACK SHELL
	6.0ø	BACK SHELL
○	5.0ø	BACK SHELL (STANDARD)
		COVER DIM.

**TABLE A**

- SPECIFICATIONS:**
1. RATION: 100V AC 1A MAX or 12V DC 2A MAX.
  2. INSULATION RESISTANCE: 50M OHM MIN at 250V DC.
  3. DIELECTRIC STRENGTH: 250 V AC / 1 MINUTE.
  4. CONTACT RESISTANCE: 30M OHM MAX.
  5. INSERTION FORCE: 4.5KG MAX.
  6. WITHDRAWAL FORCE: 0.9KG ~ 3KG.
  7. OPERATING TEMPERATURE: -20°C ~ 105°C

RoHS Compliant

大 廣 有 限 公 司  
DA KOANG CO., LTD.

TOLERANCES	PART NUMBER
.X± 0.1 .XXX±	<b>2006SER</b>
.XX± 0.05 ANGLES	

DRAFT	SCALE	DESCRIPTION
mm		Mini Din, y Jack Ass'y

CHECK	REV.
Maggie 012507'	111710'

APPROVAL	SHEET
Janne Hung Danny Hsu	1/1