



|                          |                      |    |
|--------------------------|----------------------|----|
| OPERATING VOLTAGE        | 1000V/m/n            |    |
| CURRENT                  | AC:0.5A/15V          |    |
| MAXIMUM JAW OPENING      | 5                    |    |
| OPERATING TEMPERATURE    | -40~+60 ° C          |    |
| ELECTRICAL SPECIFICATION |                      |    |
| REV.                     | PART NO.& SAMPLE NO. | BY |
| A                        | 6119                 |    |
| B                        |                      |    |

|   |  |            |
|---|--|------------|
| TOLERANCE   | SIGNATURES   | DATE       |
| 0 - 10 ±0.05<br>10 - 99 ±0.1<br>100 - 999 ±1.0<br>1000 - 9999 ±100.00<br>10000 - 99999 ±1000.00 | DRAFT: ZHOU XIN GUO<br>CHECKED: XU FU YOU<br>APPROVAL: | 29-08-2014 |
| SHEET OF  | SCALE UNIT   | REV.       |
|   | mm   | ∅          |

|                                   |                                |
|-----------------------------------|--------------------------------|
| 大 廣 有 限 公 司<br>DA KOANG CO., LTD. |                                |
| TITLE                             | Banana Plug To 2x1C Test Clips |
| CUSTOMER                          |                                |