



RAV 改版	CHANGE DESCRIPTION 記 錄 說 明	REVISED 修版者	APPROVED 審 核	DATE 日 期

SPECIFICATIONS

Technical drawing of a 1x12 connector. The side view (top) shows a rectangular component with a width of 12.0 and a height of 3.9. The length is labeled as A. The end view (bottom) shows the component's profile with a width of 8.3 and a height of 7.7. The side view also shows a series of pins with a pitch of 5 and a 1x12 pin configuration.

負載電壓	Rated Voltage	AC300V
負載電流	Rated Current	10A
塑膠本體	Housing Material	Polyamide66
焊 針	Solder Pin	□ 1.0mm, Brabb, Tin Plated
操作溫度	Operating Temperature	-40℃+105℃
PC板孔徑	PCB Hole Diameter	Ø1.5mm

POLE	2	3	4	5	6	7	8	9	10
A	12.0	17.0	22.0	27.0	32.0	37.0	42.0	47.0	52.0
B	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0

POLE	11	12	13	14	15	16
A	55.0	60.0	65.0	70.0	75.0	80.0
B	50.0	55.0	60.0	65.0	70.0	75.0

UNIT	SCALE	大 廣 有 限 公 司 DAKOANG CO., LTD.			
單位	比例				
MM					
TOLERANCE					
公差					
X.X ± 0.1	FINISH		TITLE		30501
X.XX ± 0.1	處理：		黃 銅		
	DESIGN				
ANGLE	設計：		PART NO		
角度	APPR		料號：		
		核准：	DRAW NO	圖號：	REA
					版次
					A