



ELECTRICAL CHARACTERISTIC

(1)	CONTACT RESISTANCE: $\leq 20m\Omega$
(2)	INSULATION RESISTANCE: $\geq 10M\Omega$
(3)	WITHSTAND VOLTAGE: DC300V
(4)	CURRENT RATING: 5A/DC150V
(5)	OPERATING TEMPERATURE: $-30^{\circ}C \sim 60^{\circ}C$

5	EARTHING PATCH	Fe	Gold
4	SHELL	ABS	
3	WASHER	Fe	Gold
2	NUT	Cu	Gold
1	BODY	Cu	Gold
ITEM	DESIGNATION	MATERIAL	Finish
REV	PART NO. & SAMPLE NO.	DATE	BY
A	3037A		
B			

TOLERANCE	0 - 10 10 - 99 100 - 999 1000 - 9999 10000 - 99999	± 0.05 ± 0.5 ± 1.0 ± 100.00 ± 1000.00
SIGNATURES	DRAFT: cheng huan CHECKED:	10.01.15

SHEET	SCALE	UNIT	REV
OF	1:1	mm	\emptyset

大廣有限公司
DA KOANG CO., LTD.

TITLE	Banana Jack (Red/Black)
CUSTOMER	Gold Plated